Rhode Island Recommended

SEPTIC SYSTEM FUNCTIONAL INSPECTION REPORT¹

as described in Septic System Checkup: The Rhode Island Handbook for Inspection

Inspection Date:_

	T INFO s Name	RMATIO	V	Phone #
Inspec	tion Str	eet Addre	ess & Tow	/n
		I NFORM ame		
				Phone #
Street	Addres	s & Towr		
Th <i>in no</i> พ	is inspe /ay a gua	arantee or	warranty	es the present condition of the system based on state-recommended inspection procedures, but is of future performance. The inspection report excludes and does not intend to cover components e not observable. Dry wells are not included in this inspection.
HON	<i>NEOW!</i>	NER/OCC	UPANT R	RECORDS & DATA, As Available (chapter 2) ²
respor prope Ind that ar indica	nsible for rty owner icate who ny of the te not ap	record and r. ether the fo following se plicable (N/	data accura llowing infor ervices were (A). If the pr	his section is to be provided voluntarily and at the discretion of the property owner. The property owner is solely acy and completeness. The inspector assumes no responsibility for the accuracy of information provided by the rmation was made available during the inspection. Attach copies of available records. If the property owner states not provided—or in the case of application records that the system was installed prior to regulations (1968) — roperty owner states that partial records were provided, indicate "partial."
Recor	ds and da	ords & Data ata were giv rty owner	en to the in	spector by; Realtor Other
Applic Yes □	No	cords N/A		Applications for septic system (inclusive of new systems, alteration, repairs). Indicate the number of each: New system Alteration Repairs
				Certificate of construction
				Certificate of conformance
Use R	ecords			
Yes □	No	N/A	Partial	Last two septage pumping bills
				Water bills for the last 12-24 months
	enance F	Records		
Yes	No	N/A	Partial	Maintenance inspection reports
	ent Data		the inspect	ted residence housed year-round occupants
	umber _			nber

- The Functional Inspection Report is primarily intended for inspection as part of a property transfer or sale. Chapter and section numbers refer to Septic System Checkup: The Rhode Island Handbook for Inspection.

IN-HOME PLUMBING EVALUATION (chapter 3)
Information reported in this section may in part be based on homeowner records and data. The inspector assumes no responsibility for inaccurate records or data.

Wastewa Yes	iter Routin No	g (section 3						
			All grey and black water plumbing is routed to the ISDS. Comments:					
Occupan Yes	No	Use (section Inconclus						
			potential plumbing problems gallons were used by occupants during months. Current occupancy is estimated to be over 2 occupants per bedroom, which may be stressful to the system. Owner data indicates there were live-in occupants during previous months. Based on in-home observations, there are bedrooms.					
			A garbage disposal is routed to the septic system and may place an added burden on it (section 6.1.3).					
	gnosis (sec		nd and inspected (indicate #): toilets bathtub faucets basin faucets showerheads					
Yes □	No	Inconclus	ve					
			A water treatment appliance backflushes to the septic system. There is evidence of plumbing leakage from: toilet, basin faucet, bathtub faucet, showerhead or water treatment					
			appliance. (Circle one or more of the aforementioned.) Indicate floor and room:					
SYSTEN	COMP	ONENT E	TVALUATION (chapters 1 and 5)					
Type of se	eptic syster	n (section 1	.2): Single Cesspool Conventional septic tank system Other					
Type of ta	ank, if pres	ent (section	1.2.2):					
Indicate it	f any of the effluent pu	following o	components or accessories are present: D-box handhole Effluent filter In-door lift pump Other					
Access to	a. Outlinb. Use sv	e approxim ving-tie mea	elow or attach existing drawings): At grade Below grade ate shape of the house, indicate front (F) and back (B). Assurements to indicate the manhole (main access) of the septic tank, if buried. In an access of the septic tank, if buried. In an access of the system.					
Cesspools	. hefore n	umnout an	d dye tracing (section 5.3)					
Yes	No	Not Observ						
			-					
ш			There may be an overflow, second cesspool, soil absorption system, or other outlet from the cesspool. Dye tracing is recommended (section 5.3.3).					
			There is standing water in the cesspool above the invert (section 5.3.1).					

Septic Tai	nk, <i>before</i>	pumpout,	flow trial and dye tracing (section 5.1)
Yes	No	Not Obser	
			There is evidence of structural damage to the baffles, tees or superstructure of the tank (circle one or more)(section 5.1.8).
			Based on visual observations, sewage or septage may bypass the soil absorption system via a pipe or other conveyance. If a flow trial is being done, dye tracing should also be done (section 5.6.1).
			Flowage was seen or heard coming from the inlet even though all known water-use appliances/fixtures in the home are off. This condition may indicate in-home plumbing leakage (section 5.1.8). See also "In-Home Plumbing Evaluation" (chapter 3)
			Scum and sludge layer thickness measurements were taken. Scum is ins. and sludge is ins. Indicate the appropriate "Recommended Action" in the Pumpout Guidelines table which follows (section 5.1.2).

Pumpout Guidelines for Conventional Systems (Table 5.1a)

Solids 4 Depth Criteria	8 inch depth tank Nonstandard depth tank	Recommended Action		
Combined solids < 16 inches	Combined solids < 1/3 flow depth	Pump at owners discretion. Consider setting a new Maintenance Inspection Schedule (see section 6.5 "Evaluation of Inspection Schedules."		
Combined solids = 16 - 34 inches	Combined solids = 1/3 - 3/4 flow depth	Pump the tank and re-inspect as per section 6.5 "Evaluation of Inspection Schedules."		
Either: Combined solids > 34 inches, Sludge > 26 inches, or Scum > 11 inches	Either: Combined solids > 3/4 flow depth, Sludge > 1/2 flow depth, or Scum 1/5 flow depth	Pump the tank and consider a system analysis by a licensed designer. A new inspection schedule, which accounts for system capacity and use, should be set by the licensed designer.		

SITE OBSERVATIONS (section 5.4)

Yes	No	Inconclusive Impermeable surface such as concrete, asphalt, or brick is located approximately over the soil absorption system.
		There are one or more of the following signs of system malfunction present: Septic odors Ponding or wastewater breakout Burnt out grass or ground staining over the soil absorption system (only indicate if one or more other signs are present). Patches of lush green grass over the soil absorption system (only indicate if one or other signs are present).
		Trees, large shrubs or other plants with extensive root systems were observed in the vicinity (10 feet as per Rule 11.06(2) of the ISDS Regulations) of the soil absorption system.
		Heavy objects (e.g. cars or pools); or evidence from such objects (e.g. tracks and impressions) are in the vicinity (i.e. directly over) of the soil absorption system.
		Stormwater, sump pumps, foundation drains or roof runoff is diverted to flow into the septic system.
		An apparent cave-in or exposed component was identified. A flow trial is not recommended.

FLOW TRIAL AND DYE TRACING (section 5.5 and 5.6)

Flow tria	l (75 gals/bdrm. @ 5 - 10 gpm with less than 2 inch rise in septic tank fluid level (section 5.5))
	Preliminary evaluation indicates that a flow trial should be performed at the septic tank outlet for any of the following reasons (indicate one or
	more; section 5.5.1): Excessive depth of septic tank solids Structural damage No solids depths measured and no pumpout in over three years
	Flow trial shows the system accepted gals. over mins. (flow trial volumes are approximates), which is: At least 75 gals/bdrm Is less than 75 gals/bdrm.
	Flow trial results were inconclusive for the following reasons (section 5.6.1):
	ng, when indicated (section 5.6)
	one of the following: Dye tracing was not done, as no potential system bypasses were identified (sections 5.6.1 and 5.6.2).
	Potential bypass(es) was/were identified but no dye tracing was performed for the following reasons (sections 5.6.1 and 5.5.1):
	Dye tracing was performed as potential system bypasses had been identified. Dye tracing results were as follows: No bypasses were confirmed.
	bypasses were confirmed originating from inside the home and bypasses were confirmed that originate outside the home.
	Describe where bypasses originate and terminate:
RESULT	S & RECOMMENDATIONS
Results:	
	n revealed (indicate one or more of the following):
	System functions properly.
	System is substandard or has substandard components. (Note reason(s) for indicating this on comment line below. Substandard systems may include, but are not limited to, cesspools, metal tanks, round tanks, undersized systems, and improper setbacks.)
	Structural damage to the system (such as cracks in the septic tank or a soil absorption system cave-in).
	Excessive wastewater backup in the soil absorption system. Plumbing leaks or wastewater routing problems in the home.
	Need for system maintenance.
	Due to the condition of the system or lack of information, the inspection results are inconclusive.
Commen	ts:

The system	n was last inspected or pumped on (indicate date or N/A if there is no knowledge of previous maintenance) based on:
Pump	ing bill Inspection report Other
	endations:
	ne or more of the following: Further evaluation by a repair professional is recommended.
	System upgrade should be considered.
	Evaluation by a plumber is recommended. Pumping and completion of the inspection is recommended.
Indicate o	ne of the following (chapter 6)
	Based on this inspection, the recommended maintenance interval is (years) and should occur on (date). The system should receive further evaluation before a next inspection is scheduled.

Standard Inspection Schedules for Single-Family Residences on Conventional Systems (section 6.1.1)

Tank Size (gallons)	Household Occupancy				
	1-4	4-6	6-8	10 →	
1000	5	3	Undersized Tanks		
1250	5	4	3	1	
1500	5	5	4	3	

Please note: Substandard systems such as cesspools and systems with metal or undersized tanks should be on 1-3 year schedules, as should rental and seasonal properties. Innovative and alternative system should be scheduled based on DEM requirements.

Adjusted Inspection Schedules for Conventional Systems (section 6.5)

TO ITICIT LANK	ds Accumulation nonstandard depth tank	System Pumped 3 Years Ago	System Pumped 4 Years Ago	System Pumped
30"- 34"	3/5- 3/4 of flow depth	System Analysis Required		5 Years Ago
26"- 30"	1/2- 3/5 of flow depth	74000 Analysis Re		3 years
21"- 26"	2/5- 1/2 of flow depth	3 years	3 years	4 years
6"- 21"	1/3- 2/5 of flow depth		4 years	5 years
16"	< 1/3 of flow depth	4 years	5 years	5 years
	1 170 of now depth	5 years	5 years	5 years

< 16"	7/3- 2/3 of flow depth	4 years	5 years
	< 1/3 of flow depth	5 years	5 years
INSPECTOR SIGNATURE Inspector's Name (printed or t			

Inspector's Signature